



SOUTHWIND

FLOORS FOR LIFE

PRODUCT SPECIFICATION

Style Number	W030D
Style Name	Authentic Plank
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	8mm (4.5mm WPC/1.5 IXPE/ 2mm Vinyl top)
Attached Cushion	1.5mm IXPE Cross Linked Polyethylene

FEATURES

Plank Edge	V Groove Painted Design
Texture	EIR (Embossed in Register)
Plank Size	9" x 60"
Installation	Floating

TESTING

Impact Sound Conduction / ASTM E492-09	IIC 62
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D2047	0.70 Dry
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E662	Pass, <450

WARRANTY

LIFETIME RESIDENTIAL
10 YEAR COMMERCIAL

ENVIRONMENTAL

Indoor Air Quality	GREENGUARD Gold certified FloorScore® certified
--------------------	--

6/16/2021 JD

available at JEVIMA Premium Flooring

at LVTflooringStore.com
office@jevima.com
717-478-8653